

SC Series

Magnetic Contractor 3 phase



Feature

- Electrical life: 2,000,000 operations (SC-N3 or smaller)
- Bifurcated auxiliary contacts for greater reliability
- Compliance with international standards (UL, CSA, IEC, LR, BV, etc)
- Easier to use (structured to enable easy coil replacement)
- High operating reliability due to a super magnet with built-in IC (SC-N6 or larger)
(Prevents coil burning due to voltage fluctuations and contact fusing due to floppy operation; enables using the same coils for AC/DC, increase the range, reduces switching noise, etc)
- Mirror contacts are a standard feature
- A wide range of options

SC Model	AC3, IE947-4-1		Rated Operational		Auxilliary		*Coil Voltage					Unit Price (THB)
			Current (A)		Contact							
	200-220V	380-440V	200-220V	380-440V	NO	NC	24V	48V	120V	240V	400V	
SC-03	2.5	4	11	9	1	-	x	x	x	x	x	750
SC-0	3.5	5.5	13	12	1	-	x	x	x	x	x	830
SC-05	3.5	5.5	13	12	1	1	x	x	x	x	x	1,030
SC-4-0	4.5	7.5	18	16	1	-	x	x	x	x	x	1,230
SC-4-1	5.5	11	22	22	1	-	x	x	x	x	x	1,430
SC-5-1	5.5	11	22	22	1	1	x	x	x	x	x	1,500
SC-N1	7.5	15	32	32	2	2	x	x	x	x	x	2,170
SC-N2	11	18.5	40	40	2	2	x	x	x	x	x	2,950
SC-N2S	15	22	50	50	2	2	x	x	x	x	x	3,620
SC-N3	18.5	30	65	65	2	2	x	x	x	x	x	4,420
SC-N4	22	40	80	80	2	2	x	x	x	x	x	6,300
SC-N5A	30	55	105	105	2	2	x	x	x	x	x	6,620
SC-N6	37	60	125	125	2	2	o	o	o	o	x	9,790
SC-N7	45	75	150	150	2	2	o	o	o	o	x	14,080
SC-N8	55	90	180	180	2	2	o	o	o	o	x	16,220
SC-N10	65	110	220	220	2	2	o	o	o	o	x	21,850
SC-N11	90	160	300	300	2	2	o	o	o	o	x	29,070
SC-N12	120	220	400	400	2	2	o	o	o	o	x	43,160
SC-N14	180	315	600	600	2	2	o	o	o	o	x	91,410
SC-N16	220	400	800	800	2	2	o	o	o	o	x	132,700

NOTE : * X : Coil operating voltage AC

O : Coil operating voltage both AC or DC

- Prices are not included VAT

- Prices are subjected to change without notice