



VKF (2 แกน)

ประเภท : สายไฟฟ้าใช้งานที่แรงดันไฟฟ้าไม่เกิน
300/300 V และ 300/500 V อุณหภูมิตัวนำไม่เกิน 70°C
ชนิดตัวนำ 2 แกน
การใช้งาน : ใช้ต่อเข้าเครื่องใช้ไฟฟ้า อุปกรณ์ไฟฟ้าหรือ
ดวงโคม

มอก. 11-2553

Nominal cross sectional area (mm ²)	Class of conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter		Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ/km)	Continuous current rating in free air at 40°C maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
				minimum (mm)	maximum (mm)					
0.5	Flexible	0.5	0.6	3.0 x 4.9	3.7 x 5.9	39.0	0.012	3	26	100/C
0.75	Flexible	0.5	0.6	3.2 x 5.2	3.8 x 6.3	26.0	0.010	6	32	100/C



สี : ● ●

มอก. 11-2553

Nominal cross sectional area (mm ²)	Class of conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter		Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ/km)	Continuous current rating in free air at 40°C maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
				minimum (mm)	maximum (mm)					
0.75	Flexible	0.6	0.8	3.7 x 6.0	4.5 x 7.2	26.0	0.011	6	41	100/C
1	Flexible	0.6	0.8	3.9 x 6.2	4.7 x 7.5	19.5	0.010	10	47	100/C



สี : ● ●

“ ทุกเส้น เน้นคุณภาพ ”